MODEL BV C-Class 48"x96" Post and Beam Vacuum Forming Series

Bel-O-Vac Forming the world today

Equipment Specifications:

Belovac Industries ● 435 E. Lincoln St., Ste A ● Banning, Ca 92220-4527 Office: (951) 741-4822 ● Fax: (951) 922-1494

www.belovac.com



- Depth of draw 22 inches
- Fully adjustable material clamping
- Tooling Table: 3 1/4" (8cm)
 Pneumatic drive cylinder 300lb (136kg)
 seal pressure with adjustable slotted track for rapid tool mounting
- Solid state programmable heat timing unit, coupled with programmable percentage control unit
- Heater Panel: 63,000 watts infared radiant panel, with size-down option

- Vacuum Pump: High volume,
 Hi-vacuum pump, Onboard 60 Gallon surge tank
- Construction: Post and Beam, Modular Frame System
- Recommended for plastics
 ABS PVC PET Poly styrene kydex - Poly propylene
- Plastic gauges up to 1/4" (.64cm)

Electric Requirements:

Power requirement:220 three phase 145 amps



Option: Vacuum Former with Overhead Assist



Available Option: Air circulated drying oven; Recomended for pre-drying Polycarbonate, Raydel and the preheating of heavy gauges plastic.



Option: Production Rollholder